



Latitude Edge 11' Cable SRL-P

*See chart for part numbers, hook configurations, and product weights

FEATURES :

- Unique protective shock pack cover with mesh lining for cool-air comfort.
- Convenient harness fastener straps for added security.
- Behind-the-web bracket attaches easily.
- Durable housing for added dependability.
- 360/180° attachment point swivels for full range of motion.
- Designed for sharp leading edges with foot-level connection.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



Class
2
Anchor above or below dorsal D-ring

Product shown:
SW8008-11LE-RBHD

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 19 in. (48 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	5 ft. 7 in. (1.7 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 121 in. (307 cm)
Max. free fall distance	72 in. (152 cm)
Min. required fall clearance	17 ft. 1 in. (5.2 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Cable	3/16" galvanized steel
Bracket	Steel, aluminum (dependent on configuration)
Housing	Nylon
Hook options	Steel, aluminum, dielectric (dependent on configuration)
Shock pack	Polyester



