



## Latitude HD 11' Web SRL-P

\*See chart for part numbers, hook configurations, and product weights

### FEATURES :

- Reliable internal braking system eliminates need for external shock pack.
- Durable housing and premium webbing increase strength and longevity.
- 360/180° attachment point offers full range of motion.
- Single leg and dual leg options available.
- Available with various hook options, see chart.
- All components are Z359.12 compliant.



SKU: FS-FSP1411-W

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1 (ABOVE D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.4 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 26 in. (66 cm)
Max. free fall distance	24 in. (61 cm)
Use below d-ring	not permitted
Min. required fall clearance	5 ft. 8 in. (1.7 m)
For full clearance requirements, see user instructions	

OSHA (BELOW D-RING)	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 900 lbs. (408.2 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 19 in. (48 cm)
Max. free fall distance	36 in. (91 cm)
Use below d-ring	3 ft. (0.91 m)
Min. required fall clearance	8 ft. 1 in. (2.5 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Webbing	25mm UHMPE webbing
Housing	Aluminum
Bracket	Steel, aluminum (dependent on configuration)
Hook options	Steel, aluminum, dielectric (dependent on configuration)



