



## FS-FSP9020

### Northstar Classic LE 20' Cable SRL

\*See chart for additional part numbers, hook configurations, and product weights

#### FEATURES :

- External energy absorber for leading edge use.
- Swivel attachment point offers wide range of motion.
- High strength polymer housing resists impact.
- Braking system activates quickly to arrest fall.
- All components are Z359.12 compliant.



SKU: FS-FSP9020

USER WEIGHT CAPACITY	
ANSI	130-310 lbs. (59-140.6 kg)
OSHA	Up to 420 lbs. (190.5 kg)

STANDARD COMPLIANT WITH	
ANSI	Z359.14-2021
OSHA	1910.140, 1910.66

ANSI CLASS 1	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	≤ 42 in. (107 cm)
Actual arrest distance	≤ 37 in. (94 cm)
Max. free fall distance	24 in. (61 cm)
Min. required fall clearance	7 ft. 1 in. (2.16 m)
For full clearance requirements, see user instructions	

ANSI CLASS 2	
Max. arrest force	≤ 1,800 lbs. (816.5 kg)
Avg. arrest force	≤ 1,350 lbs. (612.3 kg)
Max. arrest distance	N/A
Actual arrest distance	≤ 99 in. (251.5 cm)
Max. free fall distance	72 in. (183 cm)
Min. required fall clearance	15 ft. 4 in. (4.7 m)
For full clearance requirements, see user instructions	

MATERIAL SPECIFICATION	
Housing	Nylon and glass fiber
Swivel carabiner	Anodized aluminum
Carabiner	Zinc plated steel
Cable	3/16" Galvanized steel
Shock pack	Polyester



